



CMCP602H Series
High Temperature 2 Socket MS Cable Assembly
IP68 Locking Collar Connector – Yellow FEP Jacket



Features:

- High Temperature Cable Assembly
- Rugged Design for Permanent Installations
- 2 Socket MS Connector, MIL-C 5015 Style
- IP68 Rated Locking Collar (Screw On)
- Viton Boot for Superior Chemical Resistance
- Yellow FEP Jacketed Cable
- UV, Oil and Chemical Resistant
- Suitable for Class 1 Division 1/2 Locations
- Braided Shield with Drain Wire
- 200°C Temperature Rating
- Lifetime Warranty

Typical Applications

Mates with Sensors Featuring a 2 Pin MS Connector

Connector Specifications

Connector Type:	2 Socket MS 5015 MIL-C 5015 Style
Shield Isolation:	Case Isolated
Locking Collar Material:	316 Stainless Steel
IP Rating	IP68

Cable Specifications

Jacket Material:	FEP (Fluorinated Ethylene Propylene)
Jacket Color:	Yellow
Insulation:	Fiberglass
Conductors:	2 Plus Drain Wire
Wire AWG:	20AWG (0.52mm ²)
Drain Wire AWG:	24AWG (0.21mm ²)
Shielding:	Braided Shield
Cable Diameter:	0.19" (4.8mm)
Weight:	0.048 Lbs/Ft (1.48kg/m)
Temperature Range:	-67 to +392°F (-55 to +200°C)
Capacitance Per Foot (pF/ft):	30pF/ft (98.42pF/m)

Optional Armor Specifications

Material:	316 Stainless Steel
Type:	Hose or Braided Armor
Diameter	Hose = 0.29" (7.37mm)
	Braid = 0.23" (5.84mm)



Cable Shown with Stainless Steel Hose Armor and Push On Connector



Cable Shown with Stainless Steel Braided Armor and Locking Collar Connector


Condition Monitoring Custom Products

Smart Condition

Distribuidor Autorizado
contacto@smartcondition.mx
www.smartcondition.mx
Cel. (493) 106 9062
Cel. (493) 114 1974

Connector Pinout / Wire Color

Color Code: A = White
 B = Back



Ordering Information:

CMCP602H	-XX	-XX	-XX	-XX	2 Socket MS Cable Assembly w/ Locking Collar (IP67)
	-16				16' (5m) Long
	-32				32' (10m) Long
	-64				64' (20m) Long
	-Specify				Specify Cable Length in Feet
		-01			Standard Cable, No Armor
		-02			Cable with Overall Stainless Steel Hose Armor
		-03			Cable with Overall Stainless Steel Braided Armor
			-01		Tinned Leads on Fly End (Terminal Block Connection)
			-02		Spade Lugs Installed on Leads (Screw Terminal Connection)
			-03		BNC Jack on Fly End
			-04		BNC Plug on Fly End
			BLANK		Isolated – Shield Not Connected at Sensor End (Standard)
			-NI		Non-Isolated – Shield Connected at Sensor End

Example Part Number:

CMCP602H-16-01-01
 2 Socket MS Cable Assembly
 16' (5m) Long
 Standard Cable, No Armor
 Tinned Leads on Fly End

Similar Products:



CMCP602HST
 Push On IP68 Connector



CMCP603H
 3 Socket Locking Collar



Distribuidor Autorizado
 contacto@smartcondition.mx
 www.smartcondition.mx
 Cel. (493) 106 9062
 Cel. (493) 114 1974